

# OS Series Lightheads

SMALL OVAL SURFACE MOUNT MULTI-PURPOSE LIGHTING



**The small solution and versatile answer for putting LED lighting virtually anywhere on your vehicle!**

Small oval LED lighthead with chrome housing and clear lens. Available in flashing or steady-burn auxiliary warning, white illumination, and marker/clearance. Add a remote LED flasher to the steady-burn warning model and choose up to 60 flash patterns.

This light is small enough to tuck just about anywhere you need additional warning or illumination. 45° angled bezel model illuminates step surfaces for a sure step every time. Extreme low amp draw lets you add as many as you want.



OSR00FCR  
OSR00SCR  
warning



OSA00FCR  
OSA00SCR  
warning




OSR00MCR  
marker/clearance




OSA00MCR  
marker/clearance



OSC0EDCR  
white illumination



OSB00FCR  
OSB00SCR  
warning



OSC00FCR  
warning

**Products Shown Actual Size!**



OAC0EDCR  
45° bezel step light  
front & side view

## FEATURES

- Warning models contain four bright LEDs and are available in two versions; flashing or steady-burn.
- Warning models are available in red, amber, white, and blue.
- Red warning certified to SAE J595, SAE J845 and Class 3. Amber and blue warning certified to SAE J845.
- Steady-burn warning requires an external LED flasher, purchased separately.
- Super-LED® Illumination light available with standard or 45° angled housing for surface or step lighting; certified to NFPA 13.10.3 surface lighting. Draws 20 MA. and produces 20 lumens.

- Marker/clearance light available in red or amber, and certified to SAE J592.
- All models include chrome plated flange and mounting gasket.
- Surface mount.
- Encapsulated for moisture and vibration resistance.
- Extremely low 30mA (avg) amp draw.
- Includes 6" wire leads.
- 5 year HDP® Heavy-Duty Professional warranty.
- Dimensions: 1" (25mm) H x 1/2" (13mm) D x 1-1/2" (38mm) L.  
OAC0EDCR: 1" (25mm) H x 7/8" (21mm) D x 1-7/8 (48mm) L.

## MODELS

- OS\*00FCR**.....4 LED warning, SingleFlash flash pattern.
- OS\*00SCR**.....4 LED warning, steady-burn.
- OSC0EDCR**....Super-LED, white illumination light.
- OAC0EDCR**....Super-LED, 45° bezel, white illumination light.
- OS\*00MCR**....4 LED, marker/clearance light, amber or red.

Replace \* in model number with color desired:  
A=Amber, B=Blue, C=White, R= Red



Whelen Engineering reserves the right to upgrade and improve products without notice.  
© 2010 Whelen Engineering Company, Inc. Printed in U.S.A.  
NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc.  
Code No. 12152C - 09/10

**WHELEN®**  
ENGINEERING COMPANY, INC.

51 Winthrop Road  
Chester, Connecticut 06412-0684  
(860) 526-9504 • Fax: (860) 526-4078  
www.whelen.com